

NPSOR-91-13
NAVAL POSTGRADUATE SCHOOL
Monterey, California



A TECHNIQUE FOR ASSESSING SHORT
BASELINE ARRAY TILT ERRORS

Robert R. Read
//

May 1991

Approved for public release; distribution is unlimited.

Prepared for:
Naval Postgraduate School,
Monterey, CA 93955

FedDocs
D 208.14/2
NPS-OR-91-13

Fed Docs
D 208.14/2: NPS-OR-91-13

NAVAL POSTGRADUATE SCHOOL,
MONTEREY, CALIFORNIA

Rear Admiral R. W. West, Jr.
Superintendent

Harrison Shull
Provost

This report was funded by the Naval Postgraduate School Research Program.

This report was prepared by:

Unclassified

Security Classification of this page

REPORT DOCUMENTATION PAGE

1a Report Security Classification UNCLASSIFIED		1b Restrictive Markings	
2a Security Classification Authority		3 Distribution Availability of Report	
2b Declassification/Downgrading Schedule		Approved for public release; distribution is unlimited	
4 Performing Organization Report Number(s) NPSOR-91-13		5 Monitoring Organization Report Number(s) NPSOR-91-13	
6a Name of Performing Organization Naval Postgraduate School	6b Office Symbol (If Applicable) OR	7a Name of Monitoring Organization Naval Postgraduate School	
6c Address (city, state, and ZIP code) Monterey, CA 93943-5000		7b Address (city, state, and ZIP code) Monterey, CA 93943-5000	
8a Name of Funding/Sponsoring Organization Naval Postgraduate School	8b Office Symbol (If Applicable) OR/Re	9 Procurement Instrument Identification Number OM&N Direct Funding	
8c Address (city, state, and ZIP code) Monterey, California 93943-5000		10 Source of Funding Numbers	
		Program Element Number	Project No
		Task No	Work Unit Accession No

11 Title (Include Security Classification) A TECHNIQUE FOR ASSESSING SHORT BASELINE ARRAY TILT ERRORS			
12 Personal Author(s) Read, Robert R.			
13a Type of Report Technical	13b Time Covered From To	14 Date of Report (year, month, day) 1991, May	15 Page Count 29
16 Supplementary Notation The views expressed in this paper are those of the author and do not reflect the official policy or position of the Department of Defense or the U.S. Government.			
17 Cosati Codes		18 Subject Terms (continue on reverse if necessary and identify by block number)	
Field	Group	Subgroup	Calibration of test ranges; propagation of errors; three-dimensional position location systems

19 Abstract (continue on reverse if necessary and identify by block number)

The coherence of three dimensional position locations determined from a splicing together of positions generated by contiguous short baseline tracking arrays is quite sensitive to the orientations of the individual arrays. These orientations can be checked with the use of long baseline methods applied to the signal arrival times at a triplet of sensors, each from a different array, but representing the same sound source. The report presents a sharp algorithm for accomplishing this. It operates in three dimensions and tests out well in the cases attempted.

0 Distribution/Availability of Abstract <input checked="" type="checkbox"/> unclassified/unlimited <input type="checkbox"/> same as report <input type="checkbox"/> DTIC users		21 Abstract Security Classification Unclassified	
2a Name of Responsible Individual R. Read		22b Telephone (Include Area code) (408) 646-2382	22c Office Symbol OR/Re

A TECHNIQUE FOR ASSESSING SHORT BASELINE ARRAY TILT ERRORS

R. R. Read

Abstract

The coherence of three dimensional position locations determined from a splicing together of positions generated by contiguous short baseline tracking arrays is quite sensitive to the orientations of the individual arrays. These orientations can be checked with the use of long baseline methods applied to the signal arrival times at a triplet of sensors, each from a different array, but representing the same sound source. The report presents a sharp algorithm for accomplishing this. It operates in three dimensions and tests out well in the cases attempted.

1. INTRODUCTION

The experimental setting and technical background are contained in references [1, 2]. It is presumed that the reader is familiar with the background. In short, consider three short baseline arrays located, approximately, at the vertices of an equilateral triangle. Each array has four hydrophone receivers, called the x , y , z , and c phones, placed at four of the corners of a cube and forming a (local) Cartesian coordinate system. The x , y , and z array arms (each having length D) are viewed as coordinate axes stemming from an origin at the c phone. The long baseline technique uses one phone from each array. For convenience of presentation we will use only the c phones, but conceptually, it matters not which phone is selected from a particular array.

A single sound source (ping) is received by each of the three c phones and, because of the synchronous nature of the data collection system, we have three sound ray transit times; call them t_1, t_2, t_3 . Also the three position locations (poslocs) are available from the short baseline processing; call them x_i, y_i and z_i for $i=1,2,3$, respectively. These are used to initialize the algorithm. All three of these locations are in the range coordinate system. I.e. the two horizontal components are measured from a common origin and the vertical (z -value) is measured from the water surface, positive downward.

Similarly we have the three entrance angles, θ_1, θ_2 , and θ_3 , each representing the estimated elevation angle of the sound ray at the c phones and measured from the horizontal. The overall goal is to modify these entrance angles in a way that will produce a common vector for the poslocs of the three arrays. (For the present we are ignoring all other sources of error and focusing on the question of array tilt.) The difference between the final and initial entrance angle at a given c phone provides an array tilt correction for the azimuthal direction of the sound source. Two such corrections for two different azimuths can be used to correct the array's two orientation angles, X_{TILT} and Y_{TILT} . In addition, the azimuth error can be used to adjust Z_{ROT} .

The entrance angle and the transit time serve as the customary inputs to ray tracing methods that return the horizontal distance and the vertical displacement of the sound source measured from the receiver location. (Ray tracing software of both the isospeed and isogradient type are contained in reference [2].) These methods can also be used in inverse fashion. E.g. reference [2] contains a program RAYFIT which takes the positions of the source and receiver as input and returns the transit time and the entrance angle as output. In the present task we use transit time, receiver location, and source depth as input and compute the entrance angle and horizontal range of the source as output.

The locations of the three c phones are known in range coordinates and from these values we can compute h_1 , h_2 , and h_3 , the horizontal distances of each phone from the position of the sound source as determined originally by the short baseline methodology. This step is necessary because ray tracing algorithms are two dimensional (range and depth).

This is the setting for the description of the algorithm which is presented in the next section. The results of testing the method are presented in section 3. Section 4 contains some discussion. Fortran source code is contained in an Appendix.

2. METHOD

The algorithm utilizes three dimensional ray tracing in an iterative way until the three poslocs (position locations) agree. The three transit times are held fixed throughout. The first step is to adjust the entrance angles so that the three vertical values are the same. This done we adjust the horizontal ranges h_1 , h_2 , and h_3 . These latter values are the radii of the three circles representing the locus of the source if the depth were correct. See Figure 1. In the second step we vary the common depth iteratively until the three circles have a common intersection point. (If there is no common intersection then some other source of error is dominating.)




Figure 1

More specifically our technique for step one is to select one of the three values: z_1 , z_2 , and z_3 ; determine which array is associated with that value and change the entrance angles at the other two c phones until all three z 's are equal to this selected value. Some care must be applied in doing this. It normally follows that the vertical component of a posloc can be reduced and the horizontal shortened by increasing the entrance angle at the phone; decreasing that angle will normally increase the depth and the horizontal. But local aberrations in the sound speed depth velocity profile could cause some mischief and in a given instance there may appear departures from the monotone pattern.

Having and maintaining a common vertical for the three poslocs allows us to proceed as follows. Above we have two versions of the three circles whose radii are the horizontal ranges. The first set represents the case in which the currently determined poslocs are too shallow. The lowering of the common level (i.e. increase the z value) will increase the radii and this can be continued until the circles intersect at a common point. The second set illustrates the case in which the common vertical level is too deep. In this case the radii must be decreased (decrease the z value) until the circles converge. In the former case the entrance angles must be lowered and in the latter they must be raised. An algorithmic description of the process follows.

Algorithm

Setting. A depth velocity sound profile is available for all sound ray tracing type operations. The locations of the three receivers (in range coordinates) are

$$A_i = \begin{Bmatrix} a_1(i) \\ a_2(i) \\ a_3(i) \end{Bmatrix} \quad \text{for } i = 1, 2, 3$$

and the three components are nominally east, north and vertical. The three initial poslocs for the sound source are

$$(x_i, y_i, z_i) \quad \text{for } i = 1, 2, 3$$

and the associated transit times and entrance angles are

$$\left. \begin{array}{l} t_i = \text{transit time} \\ \theta_i = \text{entrance angle} \end{array} \right\} \quad \text{for } i = 1, 2, 3.$$

Step 1. Seek a common vertical; adjust the horizontal ranges.

i. The original ranges are

$$h_i = \sqrt{(x_i - a_1(i))^2 + (y_i - a_2(i))^2} \quad i = 1, 2, 3.$$

- ii. Compute the horizontal distances D_{12}, D_{13} of the first array from the second and third poslocs. If either of these values are greater than h_1 , then let $z_0 = \max(z_1, z_2, z_3)$. I.e. this choice is tantamount to a presumption of case 1; all depths need to be lowered. Otherwise let $z_0 = \min(z_1, z_2, z_3)$.
- iii. Find the two arrays for which $z_i \neq z_0$ and execute the function NEWLOC for each. This program will return adjusted values for the entrance angle and the horizontal range. These values replace their original counterparts and we are positioned with inputs

$\theta_i(p)$ the adjusted entrance angles

$h_i(p)$ the adjusted horizontal ranges

and all $z_i = z_0$. The poslocs themselves are adjusted to conform to z_0 and the appropriate $h_i(p)$ with the use of their original azimuths. That is, the values x_i and y_i are updated. In most of what follows the argument p is dropped from the notation.

Caveat. At this point it is assumed that either case 1 or case 2 (see figure) is operative. It is possible that two circles do not intersect and such a condition will be discovered when an attempt is made to run the function CIRCSOLV. If that program returns the "discriminant negative" message then one must back up and vary the depth level until the condition is corrected before one can proceed. If correction is not possible then the input structure must be declared infeasible and the computations abandoned.

Step 2. Set the convergence tolerance $\varepsilon > 0$, say $\varepsilon = .01$. Choose two of the circles. Although any two will serve, the algorithm selects the two circles whose (current) adjusted poslocs are the closest. The algorithm then views these arrays, temporarily, as arrays 1 and 2. (The affixed h'_3 and $a'_3(3)$ refer to the horizontal range and vertical component of location of the third array in this temporary index system.) Solve for the two points that they have in common. The function CIRCSOLV will do this, returning (u_j, v_j) for $j = 1, 2$. The intersection that we want is the one that is closest to the horizontal location of the third array. Thus let

$$D_1 = \sqrt{(u_1 - a'_1(3))^2 + (v_1 - a'_2(3))^2}$$

$$D_2 = \sqrt{(u_2 - a'_1(3))^2 + (v_2 - a'_2(3))^2}$$

$$D_3 = \min(D_1, D_2).$$

Next determine whether the three circles have a common intersection, or whether case 1 or case 2 is operative.

Let

$$\begin{aligned}
\text{SIGN} &= 1 \quad \text{if } D_3 \geq h'_3 + \varepsilon \\
&= -1 \quad \text{if } D_3 \leq h'_3 - \varepsilon \\
&= 0 \quad \text{if } |D_3 - h'_3| < \varepsilon
\end{aligned}$$

Notice that we have case 1 if $\text{SIGN} = 1$, case 2 if $\text{SIGN} = -1$, and the three poslocs agree if $\text{SIGN} = 0$. If $\text{SIGN} = 0$ we exit the program. In so doing a new set of azimuths will be determined from the common intersection point. If $\text{SIGN} \neq 0$, set $z_{00} \leftarrow z_0$ and update z_0 with the equation

$$z_0 \leftarrow z_{00} + \text{SIGN} \cdot |1 - h'_3/D_3| (a'_3(3) - z_{00}) \cdot \text{GAM}$$

and GAM is a tuning constant to speed convergence. (For our applications $\text{GAM} = 5$ appears to work well.)

Having a new value for z_0 we must now execute NEWLOC for all three arrays. Thus use the adjusted horizontal ranges and the original azimuths to compute the adjusted poslocs; return to the beginning of Step 2.

Supporting functions

NEWLOC($\theta, t, h, z, z_0, \theta(p), h(p)$)

Inputs

- θ = elevation angle
- t = transit time
- h = horizontal range
- z = depth of posloc
- z_0 = depth goal

Outputs

- $\theta(p)$ = adjusted elevation angle
- $h(p)$ = adjusted horizontal range

Algorithm

Make the trial adjustment

$$\theta(p) \leftarrow \theta + (z_0 - z)/h.$$

Call a ray tracing program that converts the trial entrance angle $\theta(p)$ and the fixed transit time t into new values for h and z .

Return to * if $|z - z_0| \geq \epsilon$.

Otherwise set $h(p) = h$ and exit because of convergence.

QUAD(A, B, C, X_1, X_2, ER) a quadratic equation solver.

Inputs A, B, C : the coefficients of the quadratic equation.

Outputs X_1, X_2 : the real solutions,

$$D \leftarrow B^2 - 4AC$$

Flag ER if $D < 0$

$$X_1 = (-B + \sqrt{D})/2A$$

$$X_2 = (-B - \sqrt{D})/2A$$

CIRCSOLV($A_1, A_2, h_1, h_2, u_1, v_1, u_2, v_2$)

Inputs $A_1 = \begin{Bmatrix} a_1(1) \\ a_1(2) \end{Bmatrix}$ east coordinates of the two circles

$A_2 = \begin{Bmatrix} a_2(1) \\ a_2(2) \end{Bmatrix}$ north coordinates of the two circles

h_1, h_2 circle radii

Outputs (u_1, v_1) first intersection point

(u_2, v_2) second intersection point.

Code $B_0 \leftarrow h_1^2 - h_2^2 + a_1^2(2) - a_1^2(1) + a_2^2(2) - a_2^2(1)$

$$B_1 \leftarrow 2(a_1(2) - a_1(1))$$

$$B_2 \leftarrow 2(a_2(2) - a_2(1))$$

$$B_1 \leftarrow -B_1/B_2 \quad ; \quad B_0 \leftarrow B_0/B_2$$

Let

$$P_1 = 1 + B_1^2$$

$$P_2 = 2B_1(B_0 - a_2(1)) - 2a_1(1)$$

$$P_3 = a_1^2(1) + (B_0 - a_2(1))^2 - h_1^2$$

Call QUAD

$$(P_1, P_2, P_3, u_1, u_2, \text{ERR})$$

Then set

$$u_2 \leftarrow B_0 + B_1 u_1$$

$$v_2 \leftarrow B_0 + B_1 v_1$$

end.

Algebraic description of the solution for the intersection of two circles.

Given the two circles

$$[x - a_1(1)]^2 + [y - a_2(1)]^2 = h_1^2$$

$$[x - a_1(2)]^2 + [y - a_2(2)]^2 = h_2^2$$

We begin by expanding the left hand sides and then subtract the second from the first. This produces

$$2x[a_1(2) - a_1(1)] + 2y[a_2(2) - a_2(1)] = h_1^2 - h_2^2 + [a_1^2(2) - a_1^2(1)] + [a_2^2(2) - a_2^2(1)]$$

or

$$B_1 x + B_2 y = B_0$$

and B_0 , B_1 , and B_2 are defined by identification above. If we redefine $B_1 \leftarrow -B_1/B_2$ and $B_0 \leftarrow B_0/B_2$ then the linear relationship immediately above may be re-expressed as

$$y = B_0 + B_1 x$$

and this may be substituted for y in the original first circle. Thus

$$[x-a_1(1)]^2 + [B_0 + B_1x - a_2(1)]^2 = h_1^2$$

which is a second order expression in x . In standard form it is

$$P_1 x^2 + P_2x + P_3$$

where

$$P_1 = 1 + B_1^2$$

$$P_2 = 2B_1[B_0-a_2(1)]-2a_1(1)$$

$$P_3 = a_1^2(1)+[B_0-a_2(1)]^2-h_1^2$$

If the solution of this quadratic is real, then the circles intersect and the two solutions are the x -components of those two vectors. The y -components are found from

$$y = B_0+B_1x.$$

3. TESTING THE ALGORITHM

This section documents the testing of the algorithm using the six triple crossover sets available. The first five cases are for 10 May 1989 and the sixth for 6 June 1989. (They are identified as cases 1, 3, 4, 5, 6, 7; the original case 2 is defective. The originals can be found in Ref. [1], pp. 14-17.) Graphs of the DV profiles can be found in Ref. [2].

The particulars of testing are described below. A filtered central posloc is developed (data are averaged) for each array in a triple overlap pointset count. The transit time to that position is generated by our rayfitting algorithm. Then long baseline methods are used to produce the (consensus) posloc. We

also produce the azimuth and elevation angles used for all poslocs. From these we get ZROT corrections and tilt correction for the particular azimuth. Azimuth is measured counter clockwise from the east.

Remark: This methodology assumes that the array c-phone locations are correct. We used Table B.2 (corrected) of Ref. [2]. Angles are measured in radians unless otherwise specified.

Case 1 (5/10/89)	ARRAY 1	ARRAY 2	ARRAY 11	LONGBASE
posloc	23195.5	23155.2	23172.2	23180.4
	-1927.8	-1940.2	-1915.4	-1934.5
	-326.4	-382.1	-364.9	-283.4
azimuth (original)	-.439507	-2.69574	1.56684	
(longbase)	-.442562	-2.694418	1.565204	
horizontal error (ft)	16.5	25.8	20.8	
elevation (original)	.223916	.209958	.19348	
(longbase)	.234378	.233427	.211358	
error (degrees)	0.6°	1.3°	1.0°	

Case 3 (5/10/89)	ARRAY 1	ARRAY 2	ARRAY 11	LONGBASE
posloc	23101.0	23061.2	23076.8	23085.6
	-1938.2	-1949.5	-1928.8	-1944.9
	-325.2	-380.8	-352.8	-283.7
azimuth (original)	-.451718	-2.703184	1.587809	
(longbase)	-.454869	-2.701741	1.585941	
horizontal error (ft)	16.8	24.8	18.3	
elevation (original)	.228946	.205557	.196589	
(longbase)	.239260	.228152	.211792	
error (degrees)	0.6°	1.3°	0.9°	

Case 4 (5/10/89)	ARRAY 5	ARRAY 6	ARRAY 15	LONGBASE
posloc	53014.7	52981.2	53009.1	53011.3
	-2185.7	-2144.5	-2155.8	-2165.7
	-381.2	-361.0	-367.9	-327.6
azimuth (original)	-.552438	-2.655442	1.623004	
(longbase)	-.548752	-2.649183	1.622606	
horizontal error (ft)	20.3	36.8	10.1	
elevation (original)	.212758	.197559	.212733	
(longbase)	.225691	.204975	.222314	
error (degrees)	0.7°	0.4°	0.5°	

Case 5 (5/10/89)	ARRAY 16	ARRAY 17	ARRAY 26	LONGBASE
posloc	64676.0	64642.6	64637.4	64653.3
	-8633.0	-8657.7	-8647.4	-8654.7
	-351.0	-359.5	-343.8	-316.8
azimuth (original)	-.541822	-2.598895	1.529189	
(longbase)	-.548626	-2.598187	1.525426	
horizontal error (ft)	31.4	29.3	17.5	
elevation (original)	.202977	.216093	.197164	
(longbase)	.210674	.226356	.203495	
error (degrees)	0.4°	0.6°	0.4°	

Case 6 (5/10/89)	ARRAY 3	ARRAY 4	ARRAY 54	LONGBASE
posloc	38826.5	38794.9	38828.6	38811.5
	915.3	939.9	954.0	951.1
	-349.3	-363.4	-320.1	-322.3
azimuth (original)	.223151	2.842790	-1.393582	
(longbase)	.231813	2.839161	-1.397459	
horizontal error (ft)	38.8	20.0	16.8	
elevation (original)	.207200	.269114	.183713	
(longbase)	.213329	.281344	.183226	
error (degrees)	0.4°	0.7°	-0.03°	

Case 7 (6/6/89)	ARRAY 1	ARRAY 2	ARRAY 11	LONGBASE
posloc	23307.2	23265.2	23274.3	23288.6
	-2302.1	-2309.4	-2286.9	-2304.1
	-363.5	-392.5	-366.2	-298.7
azimuth (original)	-.505522	-2.607256	1.542357	
(longbase)	-.507964	-2.605552	1.538843	
horizontal error (ft)	18.7	24.0	22.4	
elevation (original)	.201174	.203625	.211814	
(longbase)	.216092	.225676	.228084	
error (degrees)	0.9°	1.3°	0.9°	

The results are rather dramatic, but cannot be taken too literally. The set of original poslocs were generated by the processing that is currently in use. Reference [2] contains an error study of this processing. It identifies some sources of systematic error including the method of initializing the ray tracing algorithm, the use of 25 ft. water layer increments, and isospeed ray tracing. The presence of such systematic errors can mask the true effect. Recall that the original poslocs in our data are averages of those poslocs in the original triple overlap region; the transit times are computed by rayfitting with five feet water layer increments and isogradient ray tracing.

The effect is illustrated in Figure 2, which treats case 5 but is representative of all the cases. The original transit times for 13 point counts in the triple overlap region of arrays 16, 17, and 26 are plotted vs. point count. The connecting traces serve to show smoothness in the original transit times. The original poslocs are rather variable. They were averaged (as were the point count numbers) to produce stability. The transit times fitted to the three averages are marked with bold gray circles in the figure. They appear




Figure 2. Transit times to C-Hydrophones

over the average point count value of 8109.3. It is clear that they do not fall on the smooth traces. Thus we have some systematic error in our angle and other assessments. The systematic errors identified in Ref. [2] surely contribute to this condition.

Remarks: The algorithm seems to work well. One should note that the effects of small errors are quite remarkable. A one-half degree error in one of the horizontal arrays arms represents about 3 inches (since the arm is 30 feet long). If the posloc is in an overlap area (say, horizontal range > 4000 feet) then the corresponding vertical posloc error is about 40 feet.

Three of the six cases involve the array triple (1, 2, 11). These cases are independent, i.e., the point count sets are quite different for cases 1 and 3; and a different date for case 7. It is encouraging to note that the computed tilt error values are consistent. This supports the previously stated concern about the effects of systematic errors.

A second independent estimate of the rotation error obtained from differing (azimuth) directions may or may not be consistent. If not, it may provide information about the array locations. But consistency is necessary to proceed with tilt corrections.

4. SUMMARY

The algorithm appears to work quite well. In all cases the convergence was rapid. In no instance was the discriminant negative. Indeed a trap for that caveat has not yet been written into the code.

As noted, the particular results themselves should not be taken too literally. The systematic errors identified for the current processing system are the most likely suspect areas. Uncertainty in the array locations is the next concern. The use of filtered poslocs in the test cases also may be contributing to some deception. These values are the centroids of the local data sets

determined by a biased processing system. Other sources of bias may be operating, e.g., drifts in the depth-sound velocity profile.

The present work is concerned only with the development and testing of the algorithm. The next step calls for some sensitivity testing. It is important to learn how the method is affected by the error sources mentioned. There is also the question of how the tool should be used. E.g., should the poslocs be filtered before or after its application. Once the behavior is well understood, we can turn to the business of designing an experiment for calibrating the array tilts.

APPENDIX. PROGRAM LONGBASE

PROGRAM LONGBASE

12/19/90

LONGBASE.FOR is a long base line POSLOC method for the triple crossover data from the Nanoose range.

A1,A2,A3 are input vectors providing locations in 3-D for the three involved C-Hydrophones. Specifically

A1(I) are the downrange (X) coordinates.

A2(I) are the crossrange (Y) coordinates.

A3(I) are the depth (Z) coordinates. (Depth is positive down orientation).

```

DIMENSION A1(3),A2(3),A3(3),X(3),Y(3),Z(3),TH0(3),T(3)
DIMENSION H(3),AR1(2),AR2(2),HP(3),THP(3),PH0(3),PH1(3)
DIMENSION XX(3),YY(3),TH00(3),AR(4)
COMMON /SET1/ L(300),VEL(300),V0(300),V1(300),DZ(300),
*      LM(300)
REAL*8 L,VEL,V0,V1,DZ,LM
REAL*8 A1,A2,A3,X,Y,Z,DZ0,AA1,AA2,P1,P2,TH0,T,Z0,Z00,H
REAL*8 D12,D13,D23,AR1,AR2,D1,D2,D3,HP,THP,PH0,PH1,TH00
REAL*8 VA,VB,UA,UB,Z1,Z2,Z3,TH1,EPS,XX,YY,RDH,DS,DM,GAM
    
```

```

INTEGER*4 DL1,DL2,DH,MARR,SIGN,AR,ERR
    
```

```

CHARACTER*15 DVNAME,OUTNAM
    
```

```

CHARACTER*1 RES
    
```

```

5      EPS = 1D-3
      ERR = 0
    
```

C GAM is a convergence tuning constant. Adjustment may speed convergence.
 GAM = 5.0D0

C Load DVT information. Adjust depth to be positive downward.

```

WRITE(*, '(A)') ' ENTER VELOCITY PROFILE: '
    
```

```

READ(*,230)DVNAME
    
```

```

OPEN(UNIT=2,FILE=DVNAME,STATUS='OLD')
    
```

```

I = 1
    
```

```

10    READ(2,220,ERR=20,END=30)L(I),VEL(I)
    
```

```

      L(I) = -L(I)
    
```

```

      I = I + 1
    
```

```

      GOTO 10
    
```

```

20    WRITE(*,*) ' ! THERE WAS AN ERROR READING THE DVT FILE ! '
    
```

```

      STOP
    
```

```

30    CLOSE(UNIT=2)
    
```

$$M = I-1$$

C Prepare for isogradient ray tracing.

C Form the set of layer midpoints

```
DO 40 I = 1,M-1
40  LM(I) = .5*(L(I) + L(I+1))
```

C Form depth increments, and all sound velocity slopes and intercepts.

```
DO 50 I = 1,M-2
DZ(I) = LM(I+1) - LM(I)
V0(I) = (LM(I+1)*VEL(I) - LM(I)*VEL(I+1))/DZ(I)
V1(I) = (VEL(I+1) - VEL(I))/DZ(I)
50  CONTINUE
LM(M) = LM(M-1) + DZ(M-2)
```

C Enter the appropriate values for the data runs.

```
WRITE(*,'(A)') ' ENTER OUTPUT FILE NAME: '
READ(*,230)OUTNAM
OPEN(UNIT=3,FILE=OUTNAM,STATUS='NEW')
WRITE(*,200)
55  WRITE(*,*) ' '
```

C Input the C-Hydrophone location values.

```
WRITE(*,'(A)') ' ENTER THE NUMBER OF THE 1ST ARRAY : '
READ(*,*)AR(1)
CALL ARRAY(AR(1),A1(1),A2(1),A3(1),ERR)
WRITE(*,*) ' '
WRITE(*,'(A)') ' ENTER THE NUMBER OF THE 2ND ARRAY : '
READ(*,*)AR(2)
CALL ARRAY(AR(2),A1(2),A2(2),A3(2),ERR)
WRITE(*,*) ' '
WRITE(*,'(A)') ' ENTER THE NUMBER OF THE 3RD ARRAY : '
READ(*,*)AR(3)
CALL ARRAY(AR(3),A1(3),A2(3),A3(3),ERR)
IF(ERR.EQ.1) THEN
WRITE(*,*) ' ! THERE WAS AN ERROR READING THE ARRAYS ! '
WRITE(*,*) ' ! PLEASE TRY AGAIN ! '
ERR = 0
GOTO 55
ENDIF
ERR = 0
WRITE(*,*) ' '
```

C Input initial POSLOC values.

```
57  WRITE(*,'(A)') ' WHICH CASE NUMBER DO YOU WANT TO RUN ? (1-7): '
READ(*,*)AR(4)
CALL POSLOC(X,Y,Z,AR(4))
58  WRITE(*,270)X(1),Y(1),Z(1)
WRITE(*,271)X(2),Y(2),Z(2)
WRITE(*,272)X(3),Y(3),Z(3)
WRITE(*,*) ' '
WRITE(*,'(A)') ' ARE THESE VALUES CORRECT ? (Y/N): '
READ(*,230)RES
```

```

WRITE(*,*)' '
IF((RES.EQ.'N').OR.(RES.EQ.'n')) THEN
WRITE(*, '(A\)' ) ' WOULD YOU LIKE TO ENTER THEM ? (Y/N): '
READ(*,230)RES
WRITE(*,*)' '
IF((RES.EQ.'y').OR.(RES.EQ.'Y')) THEN
WRITE(*, '(A\)' ) ' ENTER THE 1ST POSLOC (X,Y,Z): '
READ(*,*)X(1),Y(1),Z(1)
WRITE(*, '(A\)' ) ' ENTER THE 2ND POSLOC (X,Y,Z): '
READ(*,*)X(2),Y(2),Z(2)
WRITE(*, '(A\)' ) ' ENTER THE 3RD POSLOC (X,Y,Z): '
READ(*,*)X(3),Y(3),Z(3)
GOTO 58
ELSE
GOTO 57
ENDIF
ENDIF

```

- C Run the RAYFIT program to each of the 3 average location
C values, and return the transit times T(I), and the entrance angles TH0(I).

```

WRITE(*,*)' '
WRITE(*,*)' ! PROCESSING !'
WRITE(*,*)' '

```

```
DO 60 I = 1,3
```

```

AA1 = 0.0D0
AA2 = A3(I)
P1 = DSQRT((X(I)-A1(I))**2 + (Y(I)-A2(I))**2)
P2 = Z(I)
IEST = 0

```

```

CALL RAYFIT1(AA1,AA2,P1,P2,M,VEL,LM,DZ,V0,V1,
*          T(I),TH0(I),TH1,IEST)
TH00(I) = TH0(I)

```

```
60 CONTINUE
```

- C Compute the max dz.

```
DZ0 = MAX(DABS(Z(1)-Z(2)),DABS(Z(1)-Z(3)),DABS(Z(2)-Z(3)))
```

- C Determine horizontal ranges and azimuths.

```

DO 70 I = 1,3
H(I) = DSQRT((X(I)-A1(I))**2 + (Y(I)-A2(I))**2)
PH0(I) = DATAN2(Y(I)-A2(I),X(I)-A1(I))

```

```
70 CONTINUE
```

```

WRITE(3,280)AR(1),AR(2),AR(3),AR(4)
WRITE(3,250)A1(1),A2(1),A3(1)
WRITE(3,251)A1(2),A2(2),A3(2)
WRITE(3,252)A1(3),A2(3),A3(3)
WRITE(3,270)X(1),Y(1),Z(1)

```



```

WRITE(3,271)X(2),Y(2),Z(2)
WRITE(3,272)X(3),Y(3),Z(3)
WRITE(3,*)' '
WRITE(3,253)H(1),H(2),H(3)

```

C Begin step 1.

C Choose the initial common depth Z0.

```

D12 = DSQRT((X(2)-A1(1))**2 + (Y(2)-A2(1))**2)
D13 = DSQRT((X(3)-A1(1))**2 + (Y(3)-A2(1))**2)
IF ((D12.GE.H(1)).OR.(D13.GE.H(1))) THEN
Z0 = MAX(Z(1),Z(2),Z(3))
ELSE
Z0 = MIN(Z(1),Z(2),Z(3))
ENDIF

```

C Determine which array POSLOC has depth Z0.

```
DO 75 I = 1,3
```

```

75  IF(Z(I).EQ.Z0) MARR = I
    WRITE(3,254)DS,Z0

```

```
GOTO 720
```

```

80  D1 = DSQRT((UA-A1(DH))**2 + (VA-A2(DH))**2)
    D2 = DSQRT((UB-A1(DH))**2 + (VB-A2(DH))**2)
    D3 = MIN(D1,D2)

```

C Test for the confluence of the three circle intersections.

```
IF(DABS(H(DH) - D3).LT.EPS) GOTO 100
```

C Perform the next iteration.

```

Z00 = Z0
Z0 = Z00 + (A3(DH) - Z00)*(1 - H(DH)/D3)*GAM
DS = D3 - H(DH)

```

```

WRITE(3,254)DS,Z0
WRITE(3,253)H(1),H(2),H(3)

```

```
720 CONTINUE
```

```
DO 90 I = 1,3
```

```
IF (I.EQ.MARR) GOTO 90
```

```
CALL NEWLOC(0.0D0,A3(I),M,TH0(I),T(I),H(I),Z(I),Z0)
```

```
90 CONTINUE
```

C Step 2 control transfer.

```
IF(MARR.EQ.4) GOTO 98
```

C Adjust POSLOCs for new horizontal ranges.

```
DO 95 I = 1,3
```

```
IF(I.EQ.MARR) THEN
```

```
XX(I) = X(I)
```

```
YY(I) = Y(I)
```

```
ELSE
```



```

XX(I) = A1(I) + H(I)*DCOS(PH0(I))
YY(I) = A2(I) + H(I)*DSIN(PH0(I))
ENDIF

```

```

95  CONTINUE

```

C Find the two closest POSLOCs.

```

D12 = DSQRT((XX(1) - XX(2))**2 + (YY(1) - YY(2))**2)
D13 = DSQRT((XX(1) - XX(3))**2 + (YY(1) - YY(3))**2)
D23 = DSQRT((XX(2) - XX(3))**2 + (YY(2) - YY(3))**2)
DM = MIN(D12,D13,D23)
IF(DM.EQ.D23) THEN
  DL1 = 2
  DL2 = 3
  DH = 1
ELSEIF(DM.EQ.D13) THEN
  DL1 = 1
  DL2 = 3
  DH = 2
ELSE
  DL1 = 1
  DL2 = 2
  DH = 3
ENDIF
WRITE(3,255)DH,GAM

```

C Step 1 completed. Set control for step 2 operations only.

```

MARR = 4
AR1(1) = A1(DL1)
AR2(1) = A2(DL1)
AR1(2) = A1(DL2)
AR2(2) = A2(DL2)

```

C Find the next set of circles. Transfer to the test for confluence.

```

98  CALL CIRCSOLV(AR1,AR2,H(DL1),H(DL2),UA,VA,UB,VB)
    GOTO 80

```

```

100  CONTINUE

```

C Finalize after convergence.

```

IF(D3.EQ.D2) THEN
  VA = VB
  UA = UB
ENDIF
WRITE(3,260)UA,VA,Z0

```

C Compute new azimuths.

```

DO 110 I = 1,3
  PH0(I) = DATAN2(Y(I)-A2(I),X(I)-A1(I))
  PH1(I) = DATAN2(VA-A2(I),UA-A1(I))
  WRITE(3,261)AR(I),PH0(I),PH1(I)
  WRITE(3,262)TH00(I),TH0(I)

```

```

110  CONTINUE
      CLOSE(UNIT=3)
      WRITE(*, '(A)') ' WOULD YOU LIKE TO RUN ANOTHER CASE ? (Y/N):'

      READ(*, 230) RES
      WRITE(*, *) ' '
      IF((RES.EQ.'Y').OR.(RES.EQ.'y')) GOTO 5

      STOP

200  FORMAT(/, ' DEFINE THE LOCATION OF THE C-HYDROPHONE FOR EACH ',
      *      ' OF THE ARRAYS OF /, ' THE TRIPLE OVERLAP. PLEASE',
      *      ' NOTE THAT WE USE A POSITIVE DOWN /, ' ORIENTATION',
      *      ' FOR DEPTH. /)
220  FORMAT(5X, D8.2, 5X, D7.2)
230  FORMAT(A)

250  FORMAT(/10X, 'A1(1)=', F10.2, '   A2(1)=', F10.2, '   A3(1)=', F10.2)
251  FORMAT(10X, 'A1(2)=', F10.2, '   A2(2)=', F10.2, '   A3(2)=', F10.2)
252  FORMAT(10X, 'A1(3)=', F10.2, '   A2(3)=', F10.2, '   A3(3)=', F10.2)
253  FORMAT(10X, 'H(1)=', F11.4, '   H(2)=', F11.4, '   H(3)=', F11.4)
254  FORMAT(/10X, 'DS  =', F11.4, '   Z0  =', F11.4)
255  FORMAT(/10X, 'DH  =', I2, '   GAM  =', F4.1)
260  FORMAT(/10X, 'U   =', F10.2, '   V   =', F10.2, '   Z0  =',
*      F10.2)
261  FORMAT(/10X, 'ARR #', I2, '   PH0  =', F10.6, '   PH1  =', F10.6)
262  FORMAT(21X, 'TH00 =', F10.6, '   TH0  =', F10.6)
270  FORMAT(/10X, 'X(1) =', F10.2, '   Y(1) =', F10.2, '   Z(1) =', F10.2)
271  FORMAT(10X, 'X(2) =', F10.2, '   Y(2) =', F10.2, '   Z(2) =', F10.2)
272  FORMAT(10X, 'X(3) =', F10.2, '   Y(3) =', F10.2, '   Z(3) =', F10.2)
280  FORMAT(10X, 'ARRAYS ', I2, ', ', I2, ', and ', I2, 7X, 'CASE ', I2)
      END

```

SUBROUTINE NEWLOC(A1,A2,M,TH0,T,H0,Z,Z0)

INPUTS:

A1: HORIZONTAL COORDINATE OF SENSOR
 A2: VERTICAL COORDINATE OF SENSOR, POSITIVE DOWN
 N: INDEX OF DEEPEST LAYER USED
 TH0: ELEVATION ANGLE
 T: TRANSIT TIME
 H0: HORIZONTAL RANGE
 Z: DEPTH OF POSLOC
 Z0: DEPTH GOAL

OUTPUTS:

THP: ADJUSTED ELEVATION ANGLE
 HP: ADJUSTED HORIZONTAL RANGE

```

COMMON /SET1/ L(300),VEL(300),V0(300),V1(300),DZ(300),
*      LM(300)
REAL*8 L,VEL,V0,V1,DZ,LM
REAL*8 TH0,T,H0,Z,Z0,THP,HP,R,EPS,A1,A2,TH1

```

C Set the convergence criteria.

```
EPS = .0010D0
```

C Compute the slant range

```
DO 5 J = 2,M
```

```
IF((LM(J-1).LE.A2).AND.(LM(J).GT.A2)) N = J-1
```

```
5 CONTINUE
```

```
THP = TH0
```

```
10 CONTINUE
```

```
THP = THP - (Z0-Z)/H0
```

```
CALL ISOGRAD1(A1,A2,T,THP,N,LM,VEL,V0,V1,DZ,H0,Z,TH1)
```

```
IF (DABS(Z-Z0).GE.EPS) GOTO 10
```

```
TH0 = THP
```

```
RETURN
```

```
END
```

```
SUBROUTINE CIRCSOLV(A1,A2,H1,H2,U1,V1,U2,V2)
```

Determines the two intersection points of two circles.

INPUTS:

A1: EAST COORDINATE OF THE TWO CIRCLES

A2: NORTH COORDINATE OF THE TWO CIRCLES

H1,H2: RADIUS

OUTPUTS:

U1,V1: 1ST INTERSECTION POINT

U2,V2: 2ND INTERSECTION POINT

```
DIMENSION A1(2),A2(2)
```

```
REAL*8 A1,A2,B0,B1,H1,H2,U1,U2,V1,V2,P1,P2,P3,B,B2
```

```
INTEGER*4 ERR
```

```
ERR = 0
```

```
B0 = H1**2 - H2**2 + A1(2)**2 - A1(1)**2 + A2(2)**2 - A2(1)**2
```

```
B1 = 2*(A1(2) - A1(1))
```

```
B2 = 2*(A2(2) - A2(1))
```

```
B1 = -B1/B2
```

```
B0 = B0/B2
```

```
P1 = 1+B1**2
```

```
P2 = 2*B1*(B0-A2(1))-2*A1(1)
```

```
P3 = A1(1)**2 + (B0-A2(1))**2 - H1**2
```

```

CALL QUAD(P1,P2,P3,U1,U2,ERR)
IF (ERR.EQ.1) THEN
WRITE(*,*) ' THERE WAS AN ERROR IN QUAD SOLUTION'
STOP
ENDIF
V1 = B0 + B1*U1
V2 = B0 + B1*U2
RETURN
END

```

```

SUBROUTINE QUAD(A,B,C,X1,X2,ERR)

```

C Solves for the real roots of the quadratic equation.

```

REAL*8 A,B,C,D,X1,X2
INTEGER*4 ERR

D = B**2 - 4*A*C
IF (D.LT.0.0D0) THEN
ERR = 1
GOTO 10
ENDIF
X1 = (-B + DSQRT(D))/(2*A)
X2 = (-B - DSQRT(D))/(2*A)
10 RETURN
END

```

REFERENCES

- [1] R.R. Read, "An Investigation of Timing Synchronization Errors for Tracking Underwater Vehicles," NPS Technical Report, NPS55-90-15, July 1990.
- [2] R.R. Read, "A Study of Underwater Sound Ray Tracing Methodology," NPS Technical Report, NPS55-90-21, September, 1990.

INITIAL DISTRIBUTION LIST

Library (Code 0142) Naval Postgraduate School Monterey, CA 93943	2
Defense Technical Information Center Cameron Station Alexandria, VA 22314	2
Department of Operations Research Naval Postgraduate School Monterey, CA 93943 ATTN: Prof. Robert R. Read, Code OR-Re	20
Department of Operations Research Naval Postgraduate School Monterey, CA 93943 ATTN: Prof. R. N. Forrest, Code OR-Fo	1
Naval Postgraduate School Monterey, CA 93943 ATTN: Research Administration, Code 012	1
Department of Operations Research Naval Postgraduate School Monterey, CA 93943 ATTN: Prof. P. Purdue, Code OR-Pd	1
Department of Operations Research Naval Postgraduate School Monterey, CA 93943 ATTN: Prof. J. Esary, Code OR-Ey	1
Department of Operations Research Naval Postgraduate School Monterey, CA 93943 ATTN: Prof. O. B. Wilson, Code PH-WI	1

Department of Operations Research Naval Postgraduate School Monterey, CA 93943 ATTN: Prof. L. Johnson, Code OR-Jo	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: R. Mash, Code 50	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: R. D. Helander, Code 51	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: S. L. McKeel, Code 512	2
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: J. Knudsen, Code 5122	2
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: T. Ward, Code 5122	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: G. Olsen, Code 5122	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: J. Hall, Code 5121	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: R. Evans, Code 5113	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: L. Beer, Code 5113	1

Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: L. Bogan, Code 5111	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: D. Hutchins, Code 5232	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: J. Cain, Code 70E2	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: E. Roberts, Code 70B1	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: J. Chase, Code 70B1	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: Cmdr Dewey, Code 80	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: A. Pickard, Code 801	1
Naval Undersea Weapons Engineering Station Keyport, Washington 98345 ATTN: Larry A. Anderson, Code 71E	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: P. Correa, Code VITRO	1
Naval Undersea Warfare Engineering Station Keyport, Washington 98345 ATTN: B. Boyer, Code VITRO	1
Center for Defense Analyses 1800 N. Beauregard St. Alexandria, VA 22311	1

Center for Naval Analyses
4401 Ford Ave.
Alexandria, VA 22302-0268

DUDLEY KNOX LIBRARY



3 2768 00330436 1